

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

1 Identification

- **Product identifier**
- **Trade name:** All Weather Paintstik
- **Article number:** 14-551, 14-554
- **Recommended use and restriction on use**
- **Recommended use:** Paint
- **Restrictions on use:** No relevant information available.
- **Details of the supplier of the Safety Data Sheet**
- **Manufacturer/Supplier:**
31 Incorporated
100 Enterprise Dr.
Newcomerstown, OH 43832
Phone: (740) 498-8324
- **Emergency telephone number:**
ChemTel Inc.
(800)255-3924 (North America)
+1 (813)248-0585 (International)

2 Hazard(s) identification

- **Classification of the substance or mixture**
The product is not classified as hazardous according to the Globally Harmonized System (GHS).
- **Label elements**
- **GHS label elements:** None.
- **Hazard pictograms:** None.
- **Signal word:** Not regulated.
- **Hazard statements:** Not regulated.
- **Precautionary statements:** Not regulated.
- **Other hazards:** There are no other hazards not otherwise classified that have been identified.

3 Composition/information on ingredients

- **Chemical characterization:** Mixtures

- **Components:**

7440-50-8	copper	25-50%
8001-26-1	Linseed oil	25-50%
7429-90-5	aluminum	10-25%
1333-86-4	carbon black	2-5%

- **Additional information:** For the wording of the listed Hazard Statements refer to section 16.

(Cont'd. on page 2)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 1)

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:**
Wash with soap and water.
If skin irritation is experienced, consult a doctor.
- **After eye contact:**
Rinse opened eye for several minutes under running water.
Seek medical treatment in case of complaints.
- **After swallowing:**
Rinse out mouth and then drink plenty of water.
Do not induce vomiting; immediately call for medical help.
- **Most important symptoms and effects, both acute and delayed:**
Headache
Nausea in case of ingestion.
Gastric or intestinal disorders when ingested.
- **Indication of any immediate medical attention and special treatment needed:**
If swallowed, gastric irrigation with added, activated carbon.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO2, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water stream.
- **Special hazards arising from the substance or mixture**
Formation of toxic gases is possible during heating or in case of fire.
- **Advice for firefighters**
- **Protective equipment:**
Wear self-contained respiratory protective device.
Wear fully protective suit.
- **Additional information:** No relevant information available.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Ensure adequate ventilation.
Wear protective equipment. Keep unprotected persons away.
For large spills, use respiratory protective device against the effects of fumes/dust/aerosol.
- **Environmental precautions**
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Methods and material for containment and cleaning up**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Pick up mechanically.

(Cont'd. on page 3)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 2)

· **Reference to other sections**

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

· **Handling**

· **Precautions for safe handling:**

Use only in well ventilated areas.
Keep away from heat and direct sunlight.
Avoid splashes or spray in enclosed areas.
Prevent formation of aerosols.

· **Information about protection against explosions and fires:** No special measures required.

· **Conditions for safe storage, including any incompatibilities**

· **Storage**

· **Requirements to be met by storerooms and receptacles:**

Store in cool, dry conditions in well sealed receptacles.
Avoid storage near extreme heat, ignition sources or open flame.

· **Information about storage in one common storage facility:**

Store away from foodstuffs.
Store away from oxidizing agents.
Do not store together with acids.

· **Specific end use(s)** No relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

7440-50-8 copper

PEL (USA)	Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume
REL (USA)	Long-term value: 1* 0.1** mg/m ³ as Cu *dusts and mists **fume
TLV (USA)	Long-term value: 1* 0.2** mg/m ³ *dusts and mists; **fume; as Cu
EL (Canada)	Long-term value: 1* 0.2** mg/m ³ *dusts and mists; **fume, as Cu
EV (Canada)	Long-term value: 0.2* 1** mg/m ³ as copper, *fume; **dust and mists
LMPE (Mexico)	Long-term value: 0.2* 1** mg/m ³ *humo (como Cu); **polvo y niebla (como Cu)

(Cont'd. on page 4)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 3)

8001-26-1 Linseed oil

OEL (Canada)	Short-term value: 10* 3** mg/m ³ *Mist **Respirable mist
TWA (Canada)	Short-term value: 10* 3** mg/m ³ *Mist **Respirable mist

7429-90-5 aluminum

PEL (USA)	Long-term value: 15*; 5** mg/m ³ *Total dust; ** Respirable fraction
REL (USA)	Long-term value: 10* 5** mg/m ³ as Al*Total dust**Respirable/pyro powd./welding f.
TLV (USA)	Long-term value: 1* mg/m ³ as Al; *as respirable fraction
EL (Canada)	Long-term value: 1.0 mg/m ³ respirable, as Al
EV (Canada)	Long-term value: 5 mg/m ³ aluminium-containing (as aluminium)
LMPE (Mexico)	Long-term value: 1* mg/m ³ A4, *fracción respirable

1333-86-4 carbon black

PEL (USA)	Long-term value: 3.5 mg/m ³
REL (USA)	Long-term value: 3.5* mg/m ³ *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV (USA)	Long-term value: 3* mg/m ³ *inhalable fraction
EL (Canada)	Long-term value: 3 mg/m ³ IARC 2B
EV (Canada)	Long-term value: 3.5 mg/m ³
LMPE (Mexico)	Long-term value: 3* mg/m ³ A3, *fracción inhalable

· Exposure controls

· Personal protective equipment:

· General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Immediately remove all soiled and contaminated clothing.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

· Engineering controls: Provide adequate ventilation.

· Breathing equipment:

Not required under normal conditions of use.

Wear appropriate NIOSH respirator when ventilation is inadequate and occupational exposure limits are exceeded.

For spills, respiratory protection may be advisable.

(Cont'd. on page 5)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 4)

· **Protection of hands:**



Protective gloves

Not required under normal conditions of use.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Eye protection:**



Safety glasses

Follow relevant national guidelines concerning the use of protective eyewear.

· **Body protection:**

Not required under normal conditions of use.

Protection may be required for spills.

· **Limitation and supervision of exposure into the environment**

No relevant information available.

· **Risk management measures** No relevant information available.

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **Appearance:**

· **Form:**

Liquid on inert carrier material

· **Color:**

According to product specification

· **Odor:**

Characteristic

· **Odor threshold:**

Not determined.

· **pH-value:**

Not applicable.

· **Melting point/Melting range:**

66 °C (151 °F)

· **Boiling point/Boiling range:**

Not determined.

· **Flash point:**

204 °C (399 °F)

· **Flammability (solid, gaseous):**

Not determined.

· **Auto-ignition temperature:**

Not determined.

· **Decomposition temperature:**

Not determined.

· **Danger of explosion:**

Product does not present an explosion hazard.

· **Explosion limits**

· **Lower:**

Not determined.

· **Upper:**

Not determined.

· **Vapor pressure:**

Not applicable.

· **Density:**

Not determined.

· **Relative density:**

Not determined.

(Cont'd. on page 6)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 5)

- | | |
|---|------------------------------------|
| · Vapor density: | Not applicable. |
| · Evaporation rate: | Not applicable. |
| · Solubility in / Miscibility with Water: | Insoluble. |
| · Partition coefficient (n-octanol/water): | Not determined. |
| · Viscosity | |
| Dynamic: | Not applicable. |
| Kinematic: | Not applicable. |
| · Other information | No relevant information available. |

10 Stability and reactivity

- **Reactivity:** No relevant information available.
- **Chemical stability:**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
To avoid thermal decomposition, do not overheat.
- **Possibility of hazardous reactions**
Toxic fumes may be released if heated above the decomposition point.
Contact with acids releases flammable gases.
Reacts with catalysts, oxidizing agents and strong alkali.
- **Conditions to avoid** Keep away from heat and direct sunlight.
- **Incompatible materials** Oxidizers, strong bases, strong acids
- **Hazardous decomposition products**
Carbon monoxide and carbon dioxide
Sulfur oxides (SO_x)
Toxic metal oxide smoke

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:** None.
- **Primary irritant effect:**
- **On the skin:** No irritant effect.
- **On the eye:** Based on available data, the classification criteria are not met.
- **Sensitization:** No sensitizing effects known.

· **IARC (International Agency for Research on Cancer):**

1333-86-4 | carbon black

2B

· **NTP (National Toxicology Program):**

None of the ingredients are listed.

(Cont'd. on page 7)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 6)

· **OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

· **Probable route(s) of exposure:**

Ingestion.

Inhalation.

Eye contact.

Skin contact.

· **Germ cell mutagenicity:** Based on available data, the classification criteria are not met.

· **Carcinogenicity:** Based on available data, the classification criteria are not met.

· **Reproductive toxicity:** Based on available data, the classification criteria are not met.

· **STOT-single exposure:** Based on available data, the classification criteria are not met.

· **STOT-repeated exposure:** Based on available data, the classification criteria are not met.

· **Aspiration hazard:** Based on available data, the classification criteria are not met.

12 Ecological information

· **Toxicity**

· **Aquatic toxicity** No relevant information available.

· **Persistence and degradability** No relevant information available.

· **Bioaccumulative potential:** No relevant information available.

· **Mobility in soil:** No relevant information available.

· **Additional ecological information**

· **General notes:**

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.

· **vPvB:** Not applicable.

· **Other adverse effects** No relevant information available.

13 Disposal considerations

· **Waste treatment methods**

· **Recommendation:**

The user of this material has the responsibility to dispose of unused material, residues and containers in compliance with all relevant local, state and federal laws and regulations regarding treatment, storage and disposal for hazardous and nonhazardous wastes.

· **Uncleaned packagings**

· **Recommendation:** Disposal must be made according to official regulations.

(Cont'd. on page 8)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 7)

14 Transport information

· UN-Number · DOT, ADR, IMDG, IATA	Not regulated.
· UN proper shipping name · DOT, ADR, IMDG, IATA	Not regulated.
· Transport hazard class(es) · DOT, ADR, IMDG, IATA · Class	Not regulated.
· Packing group · DOT, ADR, IMDG, IATA	Not regulated.
· Environmental hazards · Marine pollutant:	No
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **United States (USA)**
- **SARA**

· **Section 302 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

7440-50-8 copper

7429-90-5 aluminum

7440-66-6 zinc metal

· **TSCA (Toxic Substances Control Act)**

All ingredients are listed.

· **Proposition 65 (California)**· **Chemicals known to cause cancer:**

Reference to carbon black is based on unbound respirable particles and is not generally applicable to product as supplied.

1333-86-4 carbon black

(Cont'd. on page 9)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 8)

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients are listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients are listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients are listed.

· Carcinogenic categories**· EPA (Environmental Protection Agency):**

7440-50-8 copper

D

7440-66-6 zinc powder -zinc dust (stabilized)

D, I, II

· IARC (International Agency for Research on Cancer):

Reference to carbon black is based on unbound respirable particles and is not generally applicable to product as supplied.

1333-86-4 carbon black

2B

· NIOSH-Ca (National Institute for Occupational Safety and Health):

1333-86-4 carbon black

· Canadian Domestic Substances List (DSL):

All ingredients are listed.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Date of preparation / last revision July 07, 2017 / -**· Abbreviations and acronyms:**

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

CAS: Chemical Abstracts Service (division of the American Chemical Society)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bio-accumulable, Toxique

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety and Health

OSHA: Occupational Safety & Health Administration

· Sources

Website, European Chemicals Agency (echa.europa.eu)

Website, US EPA Substance Registry Services (ofmpub.epa.gov/sor internet/registry/substreg/home/overview/home.do)

Website, Chemical Abstracts Registry, American Chemical Society (www.cas.org)

Patty's Industrial Hygiene, 6th ed., Rose, Vernon, ed. ISBN: 978-0-470-07488-6

Casarett and Doull's Toxicology: The Basic Science of Poisons, 8th Ed., Klaasen, Curtis D., ed., ISBN: 978-0-07-176923-5.

Safety Data Sheets, Individual Manufacturers

SDS Prepared by:

ChemTel Inc.

(Cont'd. on page 10)

Safety Data Sheet

acc. to OSHA HCS (29CFR 1910.1200) and WHMIS 2015 regulations

Printing date: July 07, 2017

Revision: July 07, 2017

Trade name: All Weather Paintstik

(Cont'd. of page 9)

1305 North Florida Avenue
Tampa, Florida USA 33602-2902
Toll Free North America 1-888-255-3924 Intl. +01 813-248-0573
Website: www.chemtelinc.com